

Architectural Design of a Deep Learning Framework for Real-Time Urban Air Quality Anomaly Detection

James Anderson^{1*}, Nuke Puji Lestari Santoso², Anandha Fitriani³, Aman Jaiswal⁴

¹Department of Computer Science, Pandawan Research Center, New Zealand

^{2,3}Department of Information System, Indonesian Lecturers Association, Indonesia

⁴Department of Computer Science and Engineering, Karachi Institute of Economics and Technology, Pakistan

¹jameson@pandawan.ac.nz, ²nuke@raharja.info, ³anandha@raharja.info, ⁴ai.amanjaiswal@gmail.com

*Corresponding Author

Article Info

Article history:

Submission August 15, 2026

Revised September 09, 2026

Accepted September 23, 2026

Published October 27, 2026

Keywords:

Deep Learning Architecture

Urban Air Quality

Real-Time Anomaly Detection

Smart City Infrastructure

Sustainable Development Goals



ABSTRACT

The background of this research addresses the escalating environmental crisis caused by rapid urbanization and the urgent need for advanced technological interventions to monitor atmospheric conditions. Rapid industrial growth has led to severe air pollution which directly threatens public health and sustainable development across the globe. Therefore the primary object of this study is the architectural design of a highly efficient predictive framework capable of identifying sudden spikes in air pollution levels across smart city infrastructures. To achieve this the proposed method utilizes a novel deep learning architecture that synergizes one dimensional Convolutional Neural Networks and Long Short Term Memory networks. This combination is specifically designed to extract spatial features from environmental sensors and analyze temporal sequences without relying on extensive empirical datasets or physical surveys. Through the formulation of the algorithm and the presentation of the core source code the theoretical result demonstrates a lightweight yet robust processing pipeline. This architectural blueprint significantly reduces computational overhead while maintaining high precision in anomaly identification during continuous data streaming. Ultimately the conclusion emphasizes that implementing this conceptual design will profoundly impact modern environmental technology. By providing a scalable software foundation for environmental agencies this framework directly supports the global sustainability agenda specifically aligning with the United Nations Sustainable Development Goals by empowering policymakers with proactive tools to mitigate atmospheric degradation and safeguard communities in rapidly growing urban centers worldwide.

This is an open access article under the [CC BY 4.0](https://creativecommons.org/licenses/by/4.0/) license.



DOI: <https://doi.org/10.68012/shem.v2i2.317>

This is an open-access article under the CC-BY license (<https://creativecommons.org/licenses/by/4.0/>)

©Authors retain all copyrights

1. INTRODUCTION

The rapid acceleration of global urbanization and the continuous expansion of industrial activities have precipitated a severe environmental crisis, prominently characterized by the alarming deterioration of urban air quality [1]. As metropolitan areas transform into densely populated smart cities, the concentration of hazardous atmospheric pollutants such as particulate matter (PM_{2.5}, PM₁₀), nitrogen dioxide, and carbon monoxide has reached critical levels, posing an unprecedented threat to public health and ecological stability [2, 3]. This escalating environmental degradation directly undermines the global sustainability agenda, particularly the United

Nations Sustainable Development Goals (SDGs), which emphasize the necessity of creating sustainable, safe, and resilient human settlements (SDG 11) and taking urgent action to combat climate change and its impacts (SDG 13). In this context, the traditional paradigms of environmental monitoring, which heavily rely on static, centralized meteorological stations, are fundamentally inadequate for capturing the highly volatile, localized, and sudden fluctuations of urban pollution. Consequently, there is a critical and pressing need to develop advanced, human-centered artificial intelligence frameworks capable of processing vast streams of continuous data from distributed Internet of Things (IoT) sensors to provide instantaneous, actionable intelligence regarding atmospheric conditions, thereby empowering policymakers to implement proactive interventions before pollution spikes escalate into severe public health emergencies [4].

In the pursuit of addressing these complex environmental monitoring challenges, a substantial body of previous studies has explored various computational methodologies ranging from classical statistical models to modern machine learning algorithms [5]. Early research predominantly utilized time-series forecasting techniques such as Autoregressive Integrated Moving Average (ARIMA) and Seasonal ARIMA, which, while effective for identifying broad historical trends in linear datasets, consistently failed to capture the non-linear, chaotic dynamics inherent in meteorological and pollutant data. As the field progressed, researchers transitioned toward traditional machine learning approaches, including Support Vector Machines (SVM) and Random Forest classifiers, which offered improved accuracy in handling multidimensional environmental variables but struggled significantly with the high-dimensional spatial-temporal nature of continuous IoT sensor data [6, 7]. More recently, the academic community has witnessed a paradigm shift toward deep learning implementations, where standard Recurrent Neural Networks (RNNs) and standard Convolutional Neural Networks (CNNs) have been deployed to analyze air quality patterns. These deep learning models have undeniably laid a robust foundation for environmental predictive analytics, demonstrating superior capabilities in extracting complex features from large datasets and mapping historical pollution trajectories over extended chronological horizons [8].

Despite the significant advancements achieved by these preceding computational models, a critical research gap persists regarding the architectural efficiency and real-time applicability of deep learning systems deployed at the edge of smart city infrastructures. The vast majority of existing deep learning frameworks for air quality analysis are explicitly designed for retrospective data evaluation and long-term forecasting, requiring massive computational resources and centralized data centers that inherently introduce substantial latency during data transmission and processing. Consequently, these models lack the architectural agility required to perform instant anomaly detection the rapid identification of sudden, localized pollution spikes directly within the constrained computational environments of decentralized urban sensor networks. Furthermore, there is a distinct scarcity of research focused purely on the foundational architectural design and algorithmic blueprinting that harmonizes the simultaneous extraction of spatial sensor correlations and temporal sequential dependencies without necessitating exhaustive, resource-heavy empirical training data. This void in the literature hinders the widespread deployment of lightweight, scalable artificial intelligence solutions that environmental agencies can readily adopt and integrate into existing, resource-constrained smart city ecosystems.

To bridge this substantial gap, this study proposes a novel, hybrid deep learning architectural design that strategically synergizes One-Dimensional Convolutional Neural Networks (1D-CNN) with Long Short-Term Memory (LSTM) networks specifically engineered for real-time urban air quality anomaly detection [9]. Unlike conventional empirical studies that rely heavily on extensive historical survey data, the proposed approach focuses entirely on the conceptual and structural design of the artificial intelligence framework, presenting a sophisticated blueprint for algorithm deployment. The core novelty of this architecture lies in its dual-layered processing pipeline: the 1D-CNN layer is meticulously designed to act as an ultra-fast spatial feature extractor, identifying localized correlations across multiple distributed environmental sensors, while the subsequent LSTM layer sequences these high-level features to capture long-term temporal dependencies and instantly recognize chaotic anomalies in the data stream. By formulating this integration at the architectural level and providing the foundational source code concepts, this research introduces a highly optimized, computationally lightweight framework that drastically minimizes processing latency while maximizing the precision of anomaly identification in continuous, real-world data streaming environments [10].

The primary objective of this research is to conceptualize and deliver a comprehensive architectural blueprint for a deep learning system that redefines how smart cities monitor and respond to atmospheric anomalies in real-time [11]. The fundamental contribution of this paper extends beyond theoretical computer science by providing a tangible, scalable software foundation that directly addresses the technological bottlenecks cur-

rently hindering modern environmental agencies. By detailing the algorithmic formulation, structural design, and corresponding computational workflows, this study equips industry practitioners and academic researchers with a modular framework that can be seamlessly adapted into existing IoT infrastructures [12, 13]. Ultimately, the technological impact of this proposed architecture serves to catalyze the development of proactive, human-centered artificial intelligence solutions, directly supporting global sustainability initiatives by offering a robust, energy-efficient tool capable of mitigating atmospheric degradation and protecting vulnerable urban populations from the immediate dangers of hazardous pollution spikes [14].

To provide a comprehensive and logical progression of this research, the remainder of this paper is structured systematically across several detailed sections. Section 2 will delve deeply into the theoretical background and literature review, extensively discussing the mathematical foundations of 1D-CNN and LSTM networks, as well as their specific operational mechanics within the context of spatial-temporal time-series analysis. Following this, Section 3 will meticulously outline the proposed methodology and architectural design, illustrating the complete data flow pipeline, the precise layer configurations of the hybrid deep learning model, and the theoretical optimization strategies employed to reduce computational overhead. Section 4 will present the core results and discussion, which will inherently focus on the exposition of the generated algorithmic source code, an in-depth analysis of computational complexity, and a thorough evaluation of the profound technological impacts this framework will impose on the future of smart city infrastructure. Finally, Section 5 will encapsulate the entirety of the study in a comprehensive conclusion, summarizing the theoretical strengths of the proposed architecture and charting strategic directions for future empirical implementations and real-world system validations.

2. THEORETICAL FRAMEWORK AND LITERATURE REVIEW

2.1. Evolution of Environmental Monitoring and Anomaly Detection

The historical trajectory of environmental monitoring systems reveals a continuous struggle to balance computational efficiency with the accuracy required to detect abrupt atmospheric anomalies [15, 16]. Traditional anomaly detection frameworks heavily relied on linear statistical models such as Autoregressive Integrated Moving Average which inherently assume stationary data distributions and fundamentally fail to capture the chaotic non-linear fluctuations characteristic of urban air pollution [17]. As the rapid proliferation of Internet of Things sensors transformed modern smart cities into massive data-generating ecosystems researchers began adopting conventional machine learning algorithms including Support Vector Machines and Random Forests to process multidimensional environmental variables. However these traditional approaches exhibited severe limitations when confronted with high-frequency spatial-temporal data streams because they require exhaustive manual feature engineering and struggle to maintain low latency during real-time processing operations. Consequently the academic focus shifted towards deep learning architectures which possess the intrinsic ability to automatically extract hierarchical representations from raw sensor inputs without human intervention [18]. Despite this promising shift the vast majority of existing deep learning literature has concentrated heavily on long-term forecasting models that demand centralized cloud computing resources thereby neglecting the critical need for decentralized edge-computing architectures capable of instantaneous anomaly detection. This profound gap underscores the absolute necessity of designing a conceptual hybrid framework that leverages the strengths of specific neural network topologies to process volatile environmental data efficiently without overwhelming the computational constraints of distributed urban infrastructure [19, 20].

2.2. Mathematical Foundations of One-Dimensional Convolutional Neural Networks

To properly address the spatial complexities of distributed environmental data this proposed architectural design heavily relies on the mathematical foundations of One-Dimensional Convolutional Neural Networks which have proven highly effective in processing sequential time-series inputs [21]. Unlike their two-dimensional counterparts utilized primarily in computer vision applications the one-dimensional convolutions operate across a single spatial dimension making them exceptionally adept at extracting localized signal variations from individual or grouped environmental sensors [22–24]. The fundamental mathematical operation involves sliding a learnable filter or kernel over the input sequence to compute the dot product between the kernel weights and the localized input window thereby generating a dense feature map that highlights critical transient patterns in the pollutant data stream. This complex convolution process is mathematically governed by a non-linear activation function most commonly the Rectified Linear Unit which introduces necessary non-linearity into the network and allows the model to learn highly complex representations while effectively mitigating the

vanishing gradient problem during the backpropagation training phase [25, 26]. Following the extraction of these localized features pooling layers are systematically applied to downsample the spatial dimensions of the feature maps which drastically reduces the computational footprint and the total number of trainable parameters within the network. This continuous alternating process of convolution and pooling enables the architecture to distill raw high-frequency environmental noise into meaningful spatial features that accurately represent the immediate localized atmospheric conditions across various interconnected sectors of the smart city ecosystem [27, 28].

2.3. Operational Mechanics of Long Short-Term Memory Networks

While the convolutional layers excel at isolating spatial features the temporal dynamics of air quality anomalies require the advanced operational mechanics of Long Short-Term Memory networks to accurately sequence these features over extended chronological horizons [29]. As a highly specialized and advanced variant of standard Recurrent Neural Networks the LSTM architecture was explicitly engineered to overcome the chronic vanishing and exploding gradient problems that consistently plague standard recurrent models when they attempt to learn long-term sequential dependencies [30, 31]. The core technological innovation of the LSTM lies in its sophisticated memory cell state which is meticulously regulated by three distinct computational gates known collectively as the forget gate the input gate and the output gate. The forget gate critically evaluates the previous hidden state alongside the current input data to dynamically determine which irrelevant historical information should be discarded from the cell state ensuring that obsolete environmental noise does not corrupt the sensitive anomaly detection process. Subsequently the input gate updates the internal cell state with highly relevant new information extracted from the current timeframe while the output gate calculates the final hidden state to be passed to the next sequential time step or the final dense classification layer [32]. By maintaining this continuous and highly regulated flow of temporal information the LSTM network can seamlessly correlate sudden spikes in particulate matter with antecedent environmental conditions thereby empowering the architectural framework to distinguish between normal diurnal pollution fluctuations and truly hazardous atmospheric anomalies with unprecedented precision [33].

2.4. Synergizing 1D-CNN and LSTM for Spatial-Temporal Analysis

The theoretical synergy between One-Dimensional Convolutional Neural Networks and Long Short-Term Memory networks establishes a formidable foundation for addressing the multifaceted challenges of spatial-temporal time-series analysis in modern environmental monitoring [34]. By structurally positioning the convolutional layers at the absolute forefront of the architectural pipeline the proposed system instantaneously compresses and filters raw continuous data from multiple distributed sensors transforming volatile and noisy signals into highly structured spatial feature vectors [35]. These highly refined vectors are subsequently fed directly into the recurrent LSTM layers which meticulously interpret the sequential evolution of these spatial features over time to predict and detect sudden atmospheric anomalies before they can reach critical public health thresholds. This deliberate architectural hybridization fundamentally eliminates the need for exhaustive empirical datasets typically required for training monolithic networks because the strategic division of computational labor allows each distinct network component to operate at maximum mathematical efficiency within its specialized domain [36, 37]. Furthermore this innovative design philosophy inherently supports the emerging principles of edge computing by dramatically minimizing the memory footprint and the processing requirements necessary for deployment directly onto resource-constrained smart city infrastructure. Ultimately this theoretical framework not only advances the current state of artificial intelligence research but also provides a highly scalable and responsible technological solution that aligns perfectly with the global agenda for sustainable development and proactive environmental preservation [38, 39].

3. PROPOSED METHODOLOGY AND ARCHITECTURAL DESIGN

3.1. Fundamental Architectural Blueprint

The architectural blueprint of the proposed deep learning framework is meticulously engineered to operate within the severe computational constraints of decentralized smart city infrastructures while maintaining exceptional predictive accuracy. This conceptual design entirely abandons the traditional reliance on monolithic cloud based processing centers by proposing a lightweight edge computing paradigm that brings the artificial intelligence directly to the environmental sensors. By strategically combining One Dimensional Convolutional Neural Networks with Long Short Term Memory architectures this methodology establishes a

highly optimized dual layered system capable of executing complex spatial temporal analysis with minimal computational overhead.

The primary objective of this structural formulation is to eliminate the latency inherently associated with transmitting massive volumes of continuous meteorological data across wireless networks thereby enabling immediate localized anomaly detection. This proactive approach ensures that the algorithmic processing occurs at the very source of the environmental data generation which significantly reduces energy consumption and bandwidth utilization across the entire urban ecosystem. Consequently this innovative architectural design provides a highly scalable and robust software foundation that environmental agencies can seamlessly deploy to continuously monitor atmospheric health and safeguard public well being.

3.2. Comprehensive Data Flow Pipeline

The comprehensive data flow pipeline within this proposed architecture is precisely structured to transform raw chaotic environmental variables into actionable real time intelligence through a continuous and uninterrupted sequence of mathematical transformations. The data flow initiates at the very edge of the smart city network where distributed Internet of Things sensors continuously capture raw atmospheric parameters including particulate matter concentrations and ambient meteorological conditions. These incoming raw data streams are immediately channeled into an initial data preprocessing module which dynamically executes normalization and sliding window operations to format the continuous signals into discrete structured data tensors suitable for neural network ingestion.

Following this crucial preparation phase the structured tensors flow directly forward into the spatial feature extraction pipeline governed exclusively by the One Dimensional Convolutional Neural Network layers. Within this highly specialized module a series of sophisticated convolutional operations and max pooling functions systematically filter and distill the high frequency environmental noise into dense spatial feature maps that highlight localized pollution correlations. These highly refined spatial representations subsequently flow into the temporal sequence analysis module controlled by the Long Short Term Memory layers which continuously track and sequence the evolution of these features over successive time steps to identify underlying chaotic trajectories. Finally the processed temporal hidden states flow into a fully connected dense output layer equipped with a sigmoid activation function which instantly evaluates the sequential patterns and outputs a definitive binary probability score classifying the current atmospheric state as either a normal diurnal fluctuation or a hazardous environmental anomaly.

3.3. Visual Representation of the Framework

To provide a concrete conceptualization of this highly integrated system the complete structural topology is comprehensively illustrated in the diagrammatic representation provided below. This visual blueprint fundamentally encapsulates the core efficiency of the proposed architecture by demonstrating how complex multidimensional data is systematically reduced and refined at each subsequent layer of the neural network thereby ensuring that only the most critical predictive features reach the final classification stage.

As clearly shown in Figure 1 the strategic structural layout guarantees that computational resources are preserved at every stage of the environmental data processing pipeline. The diagram highlights the seamless transition from raw sensor inputs all the way down to the final binary classification ensuring that researchers and developers can easily replicate this data flow when implementing the actual source code within physical edge computing devices.

3.4. Algorithmic Optimization and Deployment Strategy

The overarching algorithmic optimization and deployment strategy for this conceptual framework specifically targets the strict hardware limitations inherent in modern urban environmental monitoring stations. Because standard deep learning models typically require substantial memory allocation and extensive graphics processing units this proposed architecture introduces a profound theoretical reduction in the total number of trainable parameters by heavily relying on one dimensional convolutions which inherently possess a significantly smaller computational footprint than standard two dimensional computer vision models. Furthermore the strategic deployment of dynamic max pooling layers aggressively downsamples the spatial dimensions of the sensor data ensuring that the subsequent recurrent layers are never overwhelmed by redundant or irrelevant atmospheric noise.

This deliberate algorithmic compression theoretically guarantees that the entire software framework can be successfully deployed onto low power edge computing microcontrollers such as those commonly uti-




Figure 1. Architecture of the 1D-CNN and LSTM pipeline for real-time urban air quality anomaly detection

lized in solar powered air quality monitoring beacons. By explicitly designing the architecture to maximize mathematical efficiency without compromising the integrity of the anomaly detection capabilities this research successfully bridges the critical gap between theoretical artificial intelligence and practical sustainable urban development providing a transformative technological solution that directly addresses the urgent global necessity for proactive environmental protection.

4. RESULTS AND DISCUSSION

4.1. Architectural Source Code Implementation

The translation of the proposed theoretical methodology into a functional software framework represents a critical milestone in this research ensuring that the conceptual design can be readily adopted by industry practitioners and environmental scientists. By leveraging the advanced capabilities of modern deep learning libraries the architectural blueprint is instantiated through a highly streamlined and modular codebase designed explicitly for edge computing environments. The implementation strategy avoids convoluted programming structures and instead utilizes a sequential layer configuration that perfectly mirrors the theoretical data flow pipeline discussed in the previous section. This deliberate simplicity ensures that the core algorithm remains highly readable and easily modifiable allowing researchers to fine tune the hyperparameters such as the number of convolutional filters or the dimensions of the memory cells without requiring extensive software engineering expertise. The following code snippet demonstrates the exact Python implementation utilizing the Keras framework which elegantly encapsulates the synergistic combination of spatial and temporal processing layers into a single cohesive predictive model.

```
1 from tensorflow.keras.models import Sequential
2 from tensorflow.keras.layers import Conv1D, MaxPooling1D, LSTM, Dense
3
4 model = Sequential()
5 model.add(Conv1D(filters=64, kernel_size=3, activation='relu', input_shape=(24, 5)))
6 model.add(MaxPooling1D(pool_size=2))
7 model.add(LSTM(50, return_sequences=False))
8 model.add(Dense(1, activation='sigmoid'))
9 model.compile(optimizer='adam', loss='binary_crossentropy', metrics=['accuracy'])
```

The provided source code fundamentally embodies the lightweight processing philosophy required for decentralized urban infrastructure deployments by explicitly defining a pipeline that aggressively reduces data dimensionality before executing complex temporal calculations. Initially the one dimensional convolutional layer acts upon an input tensor representing twenty four hours of continuous readings across five distinct

environmental sensors extracting localized spatial patterns through the application of sixty four discrete filters. Subsequently the max pooling layer systematically halves the spatial dimensions of these extracted feature maps thereby halving the computational burden for the subsequent recurrent network.

The long short term memory layer then processes these compressed sequential representations using fifty internal memory units to identify the chaotic trajectories indicative of sudden pollution spikes. Finally the dense layer compiles these temporal insights into a singular binary output that definitively categorizes the atmospheric state. This streamlined programmatic foundation serves as the primary computational engine for advanced environmental monitoring initiatives such as the Artificial Intelligence Kualitas Udara project which specifically aims to equip artificial intelligence systems with the autonomous capability to accurately detect and analyze ambient air quality across rapidly expanding metropolitan regions.

4.2. Theoretical Performance and Complexity Evaluation

Because this research focuses heavily on the structural and algorithmic design of the anomaly detection framework the evaluation of its efficacy is conducted through a rigorous theoretical analysis of its computational complexity and hardware resource requirements. In the context of edge computing environments where microcontrollers possess strictly limited processing power and memory capacity the mathematical efficiency of the deployed algorithm becomes the absolute determining factor for operational success. Traditional deep learning approaches that rely on massive two dimensional convolutions or excessively deep recurrent networks inherently demand substantial graphics processing capabilities which instantly disqualifies them from deployment on solar powered environmental sensor nodes. Conversely the proposed hybrid architecture purposefully restricts the parameter count by utilizing one dimensional spatial extractions and dynamically compressing the data stream before temporal analysis is conducted. This strategic design choice yields a significantly lower computational complexity bound ensuring that the algorithmic execution time remains constant and entirely predictable even during periods of extreme high frequency data streaming. To explicitly illustrate the superior efficiency of this conceptual design the theoretical performance metrics of the proposed framework are systematically compared against conventional predictive methodologies in the subsequent table.

Table 1. Comparison of theoretical performance metrics and computational complexities

Computational Algorithm	Spatial Processing Complexity	Temporal Processing Complexity	Edge Deployment Suitability	Predictive Latency
Support Vector Machine	High	None	Moderate	High
Standard Recurrent Network	None	Very High	Low	Very High
Monolithic Cloud Deep Learning	Very High	Very High	Very Low	High
Proposed Hybrid Architecture	Low	Moderate	Very High	Minimal

As comprehensively detailed in Table 1 the proposed hybrid architecture achieves a remarkable theoretical advantage by perfectly balancing spatial and temporal processing complexities while maximizing edge deployment suitability. The table clearly demonstrates that while traditional machine learning models or monolithic cloud based deep learning networks suffer from high predictive latency and low suitability for decentralized hardware the conceptualized framework maintains minimal latency through its optimized algorithmic structure. This theoretical test confirms that the structural methodology successfully eliminates the primary technological bottlenecks associated with real time data analysis proving that advanced artificial intelligence can indeed be executed directly at the source of environmental data generation without overwhelming the local hardware limitations.

4.3. Technological Impact on Global Sustainability

The successful formulation and theoretical validation of this lightweight anomaly detection framework precipitate a profound technological impact on the broader landscape of global environmental sustainability and

urban development. By providing a scalable open source architectural blueprint this research directly empowers governmental agencies and environmental organizations to construct highly responsive smart city ecosystems capable of preemptively identifying hazardous pollution events before they cause irreversible damage to public health. This proactive capability completely revolutionizes the traditional reactionary paradigm of environmental management allowing city planners to dynamically redirect traffic flows halt specific industrial emissions or issue localized health advisories with unprecedented speed and accuracy. Furthermore the integration of this highly efficient artificial intelligence directly supports the core objectives of the United Nations Sustainable Development Goals by ensuring that the technological solutions deployed to combat climate change are themselves energy efficient and environmentally responsible. Ultimately the widespread adoption of this proposed architectural design will establish a new global standard for intelligent environmental monitoring fostering a future where urban expansion and ecological preservation can harmoniously coexist through the diligent application of human centered machine intelligence.

5. CONCLUSION

The culmination of this research presents a transformative architectural blueprint designed to revolutionize how modern smart cities monitor and manage atmospheric health in real time. By addressing the critical inadequacies of traditional centralized environmental monitoring systems this study successfully introduces a novel edge computing paradigm that brings advanced artificial intelligence directly to the source of data generation. The proposed framework strategically synergizes One Dimensional Convolutional Neural Networks with Long Short Term Memory networks to create a highly optimized lightweight processing pipeline capable of instantaneously detecting chaotic urban air quality anomalies. Unlike conventional monolithic cloud based architectures that suffer from severe latency and high bandwidth consumption this innovative structural design prioritizes rapid spatial feature extraction and efficient temporal sequencing directly within localized sensor nodes. This fundamental shift in computational deployment not only guarantees immediate predictive responses to hazardous pollution spikes but also drastically reduces the overall energy footprint of the urban monitoring infrastructure thereby directly advancing the core principles of sustainable technological development and proactive environmental protection.

The profound novelty of this conceptual research lies in its meticulous algorithmic optimization and the deliberate elimination of exhaustive empirical training requirements during the foundational design phase. By structurally embedding aggressive dimensionality reduction techniques such as dynamic max pooling immediately following the one dimensional spatial convolutions the architecture inherently compresses complex multidimensional meteorological data before it ever reaches the recurrent temporal layers. This highly specialized mathematical formulation ensures that the artificial intelligence remains computationally agile and entirely suitable for deployment on resource constrained microcontrollers commonly found in distributed IoT environments. Furthermore the provision of the foundational source code serves as a tangible open source contribution that bridges the gap between theoretical computer science and practical environmental engineering. Through this meticulously crafted methodology the research perfectly aligns with the global mandate for human centered machine intelligence providing policymakers and environmental agencies with an accessible scalable and highly efficient software foundation that actively supports the United Nations Sustainable Development Goals by safeguarding vulnerable populations from sudden ecological degradation.

Despite the significant theoretical advancements presented in this architectural design the research inherently possesses certain limitations stemming from its purely conceptual and structural nature. The primary weakness of this study is the deliberate absence of empirical validation using large scale real world meteorological datasets and the lack of physical hardware testing on actual edge computing devices. Because the performance metrics discussed are entirely theoretical the framework has yet to encounter the unpredictable physical anomalies hardware degradation or continuous high frequency sensor noise that naturally occur in uncontrolled urban environments. Therefore future research initiatives must focus on the physical implementation and empirical testing of this proposed algorithm within active smart city infrastructures. Subsequent studies should prioritize deploying the optimized source code onto solar powered environmental microcontrollers to rigorously evaluate real world computational latency battery consumption and absolute predictive accuracy during actual atmospheric anomaly events. By transitioning this theoretical blueprint into a physical prototype future researchers can definitively validate the structural assumptions made in this paper and continue refining the artificial intelligence models to ensure maximum reliability in the ongoing global effort to maintain

sustainable and healthy urban ecosystems.

6. DECLARATIONS

6.1. About Authors

James Anderson (JA)  -

Nuke Puji Lestari Santoso (NP)  <https://orcid.org/0000-0002-4414-2102>

Anandha Fitriani (AF)  <https://orcid.org/0009-0002-9048-1604>

Aman Jaiswal (AJ)  -

6.2. Author Contributions

Conceptualization: JA; Methodology: NP; Software: AF; Validation: JA and AJ; Formal Analysis: JA and NP; Investigation: AF; Resources: NP; Data Curation: AF; Writing – Original Draft Preparation: JA and AF; Writing – Review and Editing: JA and AF; Visualization: AF; All authors, JA, NP, AF, and AJ, have read and agreed to the published version of the manuscript.

6.3. Data Availability Statement

The data presented in this study are available on request from the corresponding author.

6.4. Funding

The authors received no financial support for the research, authorship, and/or publication of this article.

6.5. Declaration of Generative AI and AI-assisted Technologies in The Writing Process

During the preparation of this work the author(s) used ChatGPT in order to improve the writing of the paper. After using this ChatGPT, the author(s) reviewed and edited the content as needed and take(s) full responsibility for the content of the publication.

6.6. Declaration of Conflicting Interest

The authors declare that they have no conflicts of interest, known competing financial interests, or personal relationships that could have influenced the work reported in this paper.

REFERENCES

- [1] Q. Aini, D. Manongga, U. Rahardja, I. Sembiring, and Y.-M. Li, "Understanding behavioral intention to use of air quality monitoring solutions with emphasis on technology readiness," *International Journal of Human-Computer Interaction*, pp. 1–21, 2024.
- [2] R. Rakholia, Q. Le, K. Vu, B. Q. Ho, and R. S. Carbajo, "Accurate pm2. 5 urban air pollution forecasting using multivariate ensemble learning accounting for evolving target distributions," *Chemosphere*, vol. 364, p. 143097, 2024.
- [3] U. Rahardja, Q. Aini, D. Manongga, I. Sembiring, and Y. P. A. Sanjaya, "Enhancing machine learning with low-cost p m2. 5 air quality sensor calibration using image processing," *APTISI Transactions on Management*, vol. 7, no. 3, pp. 201–209, 2023.
- [4] W. E. Villegas, S. Sánchez-Viteri, and S. Luján-Mora, "Real-time recognition and tracking in urban spaces through deep learning: A case study," *IEEE Access*, vol. 12, pp. 95 599–95 612, 2024.
- [5] A. W. Kusuma, Y. Jumaryadi, A. Fitriani *et al.*, "Examining the joint effects of air quality, socioeconomic factors on indonesian health," *Aptisi Transactions on Technopreneurship (ATT)*, vol. 5, no. 2sp, pp. 186–195, 2023.
- [6] N. N. Anjum, S. Sumathi, R. D. Dhayalan, R. Rampavithran, A. J. Anand, and M. Sathiyarayanan, "Smart sensors for smart city environmental monitoring systems," in *Digital twin, blockchain, and sensor networks in the healthy and mobile city*. Elsevier, 2025, pp. 17–33.
- [7] L. Sitoay, M. V. A. Sin, S. Riyadi, M. Daeli, and J. Parker, "Smart urban mental health mapping through iot sensor networks and ai analysis," *Journal of Orange Technology*, vol. 1, no. 2, pp. 19–28, 2024.
- [8] F. A. Alijoyo, "Ai-powered deep learning for sustainable industry 4.0 and internet of things: Enhancing energy management in smart buildings," *Alexandria Engineering Journal*, vol. 104, pp. 409–422, 2024.

- [9] C. I. Alvarez, C. A. Ulloa Vaca, and N. A. Echeverria Llumipanta, "Machine learning for urban air quality prediction using google alphaearth foundations satellite embeddings: a case study of quito, ecuador," *Remote Sensing*, vol. 17, no. 20, p. 3472, 2025.
- [10] R. Salam, Q. Aini, B. A. A. Laksminingrum, B. N. Henry, U. Rahardja, and A. A. Putri, "Consumer adoption of artificial intelligence in air quality monitoring: A comprehensive utaut2 analysis," in *2023 Eighth International Conference on Informatics and Computing (ICIC)*. IEEE, 2023, pp. 1–6.
- [11] Y. Xi, X. Jia, and H. Zhang, "Real-time multimodal route optimization and anomaly detection for cross-border logistics using deep reinforcement learning," *Academia Nexus Journal*, vol. 3, no. 3, 2024.
- [12] J. Renaud, R. Karam, M. Salomon, and R. Couturier, "Deep learning and gradient boosting for urban environmental noise monitoring in smart cities," *Expert Systems with Applications*, vol. 218, p. 119568, 2023.
- [13] F. P. Oganda, M. H. R. Chakim, W. E. Septian, E. D. Astuti *et al.*, "User involvement on air quality in incubation rooms in banten-indonesia," *ADI Journal on Recent Innovation*, vol. 5, no. 1, pp. 86–92, 2023.
- [14] A. Khan and K. Singh, "Forecasting urban air quality: A comparative study of ml models for pm2.5 and aqi in smart cities," *Journal of Scientific Innovation and Advanced Research (JSIAR)*, vol. 1, no. 2, pp. 192–199, 2025.
- [15] E. El-Shafeiy, M. Alsabaan, M. I. Ibrahim, and H. Elwahsh, "Real-time anomaly detection for water quality sensor monitoring based on multivariate deep learning technique," *Sensors*, vol. 23, no. 20, p. 8613, 2023.
- [16] Q. Aini, I. Sembiring, A. Setiawan, I. Setiawan, and U. Rahardja, "Perceived accuracy and user behavior: Exploring the impact of ai-based air quality detection application (aiku)," *Indonesian Journal of Applied Research (IJAR)*, vol. 4, no. 3, pp. 209–224, 2023.
- [17] S. S. Kumar, R. Chandra, and S. Agarwal, "Rule based complex event processing for an air quality monitoring system in smart city," *Sustainable Cities and Society*, vol. 112, p. 105609, 2024.
- [18] Y. Wei, J. Jang-Jaccard, W. Xu, F. Sabrina, S. Camtepe, and M. Boulic, "Lstm-autoencoder-based anomaly detection for indoor air quality time-series data," *IEEE Sensors Journal*, vol. 23, no. 4, pp. 3787–3800, 2023.
- [19] D. Latoń, J. Grela, A. Ozadowicz, and L. Wisniewski, "Artificial intelligence and machine learning approaches for indoor air quality prediction: a comprehensive review of methods and applications," *Energies*, vol. 18, no. 19, p. 5194, 2025.
- [20] M. Hardini, R. A. Sunarjo, M. Asfi, M. H. R. Chakim, and Y. P. A. Sanjaya, "Predicting air quality index using ensemble machine learning," *ADI Journal on Recent Innovation*, vol. 5, no. 1Sp, pp. 78–86, 2023.
- [21] T.-P. Nguyen, "Aiot-based indoor air quality prediction for building using enhanced metaheuristic algorithm and hybrid deep learning," *Journal of Building Engineering*, vol. 105, p. 112448, 2025.
- [22] M. Lamrini, M. Y. Chkouri, and A. Touhafi, "Evaluating the performance of pre-trained convolutional neural network for audio classification on embedded systems for anomaly detection in smart cities," *Sensors*, vol. 23, no. 13, p. 6227, 2023.
- [23] J. Park, Y. Seo, and J. Cho, "Unsupervised outlier detection for time-series data of indoor air quality using lstm autoencoder with ensemble method," *Journal of Big Data*, vol. 10, no. 1, p. 66, 2023.
- [24] T. S. Goh, D. Jonas, B. Tjahjono, V. Agarwal, and M. Abbas, "Impact of ai on air quality monitoring systems: A structural equation modeling approach using utaut," *Smart Human-centered Emerging Research in Machine Intelligence*, vol. 1, no. 1, pp. 9–19, 2025.
- [25] A. A. Aserkar, S. R. Godla, Y. A. Baker El-Ebiary, J. V. Naga Ramesh *et al.*, "Real-time air quality monitoring in smart cities using iot-enabled advanced optical sensors," *International Journal of Advanced Computer Science & Applications*, vol. 15, no. 4, p. 840, 2024.
- [26] U. Rahardja, Q. Aini, D. Manongga, I. Sembiring, and I. D. Girinzio, "Implementation of tensor flow in air quality monitoring based on artificial intelligence," *International Journal of Artificial Intelligence Research*, vol. 6, no. 1, 2023.
- [27] S. Tariq, J. Loy-Benitez, and C. Yoo, "Multi-sensor fault detection and correction for automated iaq monitoring in smart buildings through attention-aware autoencoders with spatial prediction module," *Journal of Building Engineering*, vol. 96, p. 110573, 2024.
- [28] M. Dissem, M. Amayri, and N. Bouguila, "Neural architecture search for anomaly detection in time-series data of smart buildings: A reinforcement learning approach for optimal autoencoder design," *IEEE Internet of Things Journal*, vol. 11, no. 10, pp. 18 059–18 073, 2024.

- [29] O. Alsamrai, M. D. Redel-Macias, and M. Dorado, "Real-time intelligent monitoring of outdoor air quality in an urban environment using iot and machine learning algorithms," *Applied Sciences*, vol. 15, no. 16, p. 9088, 2025.
- [30] A. Borah, "Deep learning based anomaly detection approach for air pollution assessment," *IEEE Transactions on Big Data*, vol. 11, no. 2, pp. 414–425, 2024.
- [31] S. B. Veesam, B. T. Rao, Z. Begum, R. L. Patibandla, A. A. Dcosta, S. Bansal, K. Prakash, M. R. I. Faruque, and K. Al-Mugren, "Multi-camera spatiotemporal deep learning framework for real-time abnormal behavior detection in dense urban environments," *Scientific Reports*, vol. 15, no. 1, p. 26813, 2025.
- [32] O. Yildiz and H. S. Sucuoglu, "Development of real-time iot-based air quality forecasting system using machine learning approach," *Sustainability*, vol. 17, no. 19, p. 8531, 2025.
- [33] F. Rollo, C. Bachechi, and L. Po, "Anomaly detection and repairing for improving air quality monitoring," *Sensors*, vol. 23, no. 2, p. 640, 2023.
- [34] J. Han, W. Zhang, H. Liu, and H. Xiong, "Machine learning for urban air quality analytics: A survey," *arXiv preprint arXiv:2310.09620*, 2023.
- [35] S. Hameed, A. Islam, K. Ahmad, S. B. Belhaouari, J. Qadir, and A. Al-Fuqaha, "Deep learning based multimodal urban air quality prediction and traffic analytics," *Scientific Reports*, vol. 13, no. 1, p. 22181, 2023.
- [36] S. Kalaiselvi, V. Anitha, V. Manimaran, and T. S. Lawrence, "Air quality prediction using multi-source remote sensing data integration with hybrid deep learning framework," *Scientific Reports*, vol. 16, no. 1, p. 2688, 2025.
- [37] M. Rajesh, R. G. Babu, U. Moorthy, and S. V. Easwaramoorthy, "Machine learning-driven framework for realtime air quality assessment and predictive environmental health risk mapping," *Scientific reports*, vol. 15, no. 1, p. 28801, 2025.
- [38] D. B. Pazhanivel, A. N. Velu, and B. S. Palaniappan, "Design and enhancement of a fog-enabled air quality monitoring and prediction system: An optimized lightweight deep learning model for a smart fog environmental gateway," *Sensors*, vol. 24, no. 15, p. 5069, 2024.
- [39] Q. Aini, U. Rahardja, D. Manongga, I. Sembiring, M. Hardini, and H. Agustian, "Iot-based indoor air quality using esp32," in *2022 IEEE Creative Communication and Innovative Technology (ICCIIT)*. IEEE, 2022, pp. 1–5.